



Fiberglass Blanket
Part#: FB64

Our 3-Ply Fiberglass Blanket comes in a red slim line cabinet complete with English/French instruction labels and pull straps for quick withdrawal. For smothering and extinguishing fires in Hospitals, Schools, Homes, and Kitchens. One-Time use only.

The fiberglass degrades at a temperature of 550°C. The standard the blanket is tested to requires that the blanket puts out the flames on a cooking oil pan and the flames cannot re-ignite within 15 minutes. The design of the Fire Blankets has a sacrificial inner film that allows the heat to escape and allow the oil to cool to prevent re-ignition.

Description:

- Patented 3-ply material – two layers of woven glass-fiber fabric with an inner layer of fire retardant film
- The essential performance of a fire blanket is to extinguish a cooking oil fire. Therefore, the blanket must:
 - Be flexible, with good draping qualities, to eliminate oxygen from the burning oil
 - Allow the oil to cool gradually to below its' self-ignition temperature, and not reignite when the blanket is removed after 17 minutes
 - Control the cooling process
- Red slim thermoplastic container
- Blanket size 72" (182 cm) x 48" (122 cm)
- Cabinet measures 16-5/8"H x 6-1/4"W x 1-1/2"D
- Pull Straps for quick blanket withdrawal
- Independently tested – BS EN 1869:1997
- Bilingual Operating Instructions