First Alert®

10 Year Life, Slim Design SMOKE ALARM

PR710A









10-YEAR LITHIUM POWERCELL

No costly battery replacement for the 10-year life of the alarm

PHOTOELECTRIC SENSOR

For less nuisance alarms

MUTE BUTTON

One button mutes unwanted alarms immediatley. Also tests alarm function.

TAMPERPROOF, SEALED ALARM DESIGN

Meets code for sealed/tamperproof alarms. Ideal for rental properties.

LOW PROFILE, ROUND DESIGN

Half the size of a standard smoke alarm

LOUD 85DB ALARM

10 YEAR WARRANTY





TECHNICAL SPECS:

Alarm Dimensions:	4.92" x .96" x 4.92"
Colour:	White
Warranty:	10 Years
Battery Life in Alarm:	72 Hours in continuous alarm
Sensor:	Photoelectric
Operating Temp Range:	4° C - 38° C
Humidity:	80% relative humidity (RH)
Audio Alarm:	85dB at 10 ft
Listing:	cETL certified
Sensor: Operating Temp Range: Humidity: Audio Alarm:	Photoelectric 4° C - 38° C 80% relative humidity (RH) 85dB at 10 ft

6.87" x 8.63" x 1.63"

SHIPPING SPECS: Individual Clam Dimensions

Units per Pallet

Cube Weight

Weight Cube	0.36 lbs (0.0543 ft ³)
UPC	029054015655 Subject to change
Master Carton Dimensions	20.61" x 25.89"x 4.89"
Master Pack	3
Weight	1.75 lbs
Cube	(0.195 ft ³)
Case UPC	10029054014778 Subject to change
Cases per Layer	48
Number of layers	5

240 (57.11 ft³)

465 lbs